



HOLA F24EN (ENG)

Outdoor sounder with flash

Description

The HOLA F24EN (ENG) is a conventional sounder designed for using outside the buildings with a high power acoustic output and a beacon signal. Is compatible with Detnov's conventional control panels and addressable sounder modules MAD-43X, and with the majority of the conventional panels in the market.

The HOLA F24EN (ENG) combines the acoustic and indicator parts in a single housing, and is activated with a single voltage input.

Features

- Settable low-consumption sounder
- Outdoor installation
- 3 settable and independent alarm inputs
- 6 sounds for alarm, pre-alarm and evacuation
- EN 54-3 approved

Applications

Within a fire protection system, alarm notification is the main function of the sounder.

Detnov's range of conventional sounders deliver an audible and/or visible notification, depending on the model, allowing the occupants of a building to be alerted of a fire or other type of emergency.

Technical features

Sounder		
Operating voltage:		From 20 to 30 VCC
Alarm current consumption at 24 V:		From 100 to 400 mA, depending on the tone
Volume at 1 m:		108,76 dB
Tone:		500 Hz / 1200 Hz
Connections		
		2 x 1,5 mm ² twisted
Environment		
Operating temperature:		From -25°C to +55°C
Relative humidity:		95% without condensation
IP Index:		IP44
Physical features		
Size:		335 mm x 220 mm x 85 mm
Material:		ABS
Approvals		
		EN 54-3
Certificate number:		1293-CPR-0551